



RAZORLITE™

REVISION: A

EFFECTIVE: 1/2025

RAZORLITE™


LED LINEAR FIXTURES FOR ELEVATORS



RAZORLITE™

Available in 0.25" inch increments up to 11 FEET LONG!

End View
Actual Size



RAZORLITE by Man-D-Tec®

CONTEMPORARY PERIMETER LED LINEAR LIGHTING FOR ELEVATORS.

LED linear lighting available in warm white or neutral white. Neutral white version provides 251 lumens per linear foot. **Inset mount into walls and ceilings, or use as a perimeter light.** Lights can be used as a direct source of light into the cab or as accents with another primary lighting system.

Available in 0.25 inch increments (up to 11 feet in length) with a wide beam angle for superior lighting in elevator cabs.

Mil-Spec aluminum extrusion. Available in mill finish or black anodized finish.

***Available with 2,700K, 3,000K or 4,000K color temp**

Product Specifications on the back of page.

RAZORLITE™

REVISION: A
EFFECTIVE: 1/2025

RAZORLITE™
SPECIFICATIONS

Fixture
(RAZORLITE™)

MATERIAL	Mil-Spec Aluminum Extrusion	
DIMENSIONS	0.83"	Overall Thickness
	0.58"	Overall Width
	6" to 132"	Overall Length (0.25" increments)
FINISH	Mill Finish Aluminum OR Black Anodized (option)	
LED COLOR	Warm White (2,700k)	
	Warm White (3,000k) STANDARD	
	Neutral White (4,000k)	
OUTPUT	251 Lumens per linear foot (Neutral white)	
LED	Wattage	5 Watts per linear foot
	Beam Angle	Approx. 105 degrees, wide angle



Mounting
Choices

MOUNTING	Inset mount into walls and ceilings, or use as a perimeter light
----------	--

Power
Supply

MATERIAL	.060 Aluminum
PART NUMBER	PS100D (Powers up to THREE RazorLite fixtures; Max 15 linear feet total)
	PS200D (Powers up to SIX RazorLite fixtures; Max 30 linear feet total)
DIMMER	INCLUDED
VOLTAGE	Input: 115 VAC (220VAC Also Available)

Emergency
(Optional)

ELS-L4™	Powers (2) two RazorLite LED fixtures up to 16 linear feet total
---------	--



MAN-D-TEC, INC.
8175 E. PARADISE LANE
SCOTTSDALE, AZ 85260

P. 480.998.0325
F. 480.998.0318

1.800.944.6263
WWW.MANDTEC.COM